






Woodcare®

Interior Varnish Satin

Product Base Code: WIVS

	Product Description					
	<p>Haymes Paint Woodcare Interior Varnish Satin is an easy-to-use product, suitable for use on natural and stained interior timber. Its hard-wearing finish resists heat and steam, making it ideal for use in areas such as kitchens and bathrooms. This durable coating preserves the natural look of timber and protects against wear and tear.</p>					
 Interior use only	 Mineral Turpentine wash-up	Key Features & Benefits				
		<table border="1"> <tr> <td>Long-lasting</td> <td>Protects surfaces against wear and tear for longer</td> </tr> <tr> <td>Easy to clean</td> <td>Low maintenance</td> </tr> <tr> <td>Harding-wearing</td> <td>Tough durable finish</td> </tr> </table>	Long-lasting	Protects surfaces against wear and tear for longer	Easy to clean	Low maintenance
Long-lasting	Protects surfaces against wear and tear for longer					
Easy to clean	Low maintenance					
Harding-wearing	Tough durable finish					
 Coverage Up to 15 sqm/L	 Recoat 8 hrs					

Where to use

Substrate : Timber-Interior, Timber-Pine Lining, Timber-Plywood and Timber-Veneer

Interior : Built-in robes/Cupboards, Doors, Furniture, Panelling, Skirting and Architraves, Trims and Window Frames

Note: Haymes Woodcare Interior Varnish is not suitable for floors or benchtops. Use Haymes Woodcare Easy Floor for these surfaces.

Typical Properties

Colour	Clear
Application method	Brush, spray, mohair roller
Gloss level	Satin
Clean-up	Mineral Turpentine
Dry time - touch dry	3 hours
Dry time - recoat	8 hours
Coverage	Up to 15 sqm/L dependent upon surface porosity, profile and method of application.
Sizes	250mL, 500mL, 1L, 4L
VOC	490 g/L
Volume solids	38%
Film build wet	67 µm

Film build dry	26 µm
----------------	-------

Precautions

- Do NOT apply if ambient temperature is less than 10°C , greater than 35°C or if temperature will drop below 10°C during the drying period.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperatures or higher humidity, drying times will be extended. Under warm conditions refer to thinning advice.
- Wear disposable or rubber gloves to avoid skin contact.
- Do NOT overwork the product. Repeatedly going over the same area may cause unattractive brush marks and result in an uneven finish.
- Soak all cloths with traces of paint or solvent in water to prevent spontaneous combustion.

Surface Preparation

Previously stained or clear coated surfaces	<ol style="list-style-type: none"> 1. If the coating is in sound condition: <ol style="list-style-type: none"> a. Clean with Haymes Unikleen, allow to dry and sand back to a dull surface. Remove dust. b. Ensure surface is clean, bare, dry and free of mould, wax, grease and other contaminants. c. Conduct an adhesion test [1], followed by a compatibility test [2], as outlined below. 2. If coating has worn back to bare timber: <ol style="list-style-type: none"> a. Sand surface to completely remove any remaining coating. Remove dust. b. Ensure surface is clean, bare, dry and free of mould, wax, grease and other contaminants. c. Follow application instructions.
New timber	<ol style="list-style-type: none"> 1. Ensure surface is clean, bare, dry and free of mould, wax, grease and other contaminants. 2. Sand timber with 240-grit sandpaper in the direction of the grain until smooth. Remove dust. 3. Follow application instructions.
Adhesion test	[1] To check the adhesion of an existing coating, cut an 'X' lightly into the coating and firmly apply adhesive tape across the cut and then remove tape. If the tape removes the existing coating, remove all previous coatings before painting.
Compatibility test	[2] Test for compatibility with a previous coating by sanding and cleaning a small inconspicuous area. Apply 1 coat of the desired topcoat and allow to dry. After 24 hours, conduct an adhesion test. If the tape removes the coating, remove all previous coatings before painting. It is recommended to conduct the compatibility test in several areas.
IMPORTANT:	You must consult the installation guide of the construction product you are using for information on coatings and finishing guide to determine product suitability prior to commencing work. For further information and product specification consult a Haymes Paint representative on 1800 033 431.

Application

- For a stain finish, apply Haymes Woodcare Wood Stain as per label instructions. Allow Wood Stain to dry for eight hours before applying Haymes Woodcare Interior Varnish.
- Stir thoroughly before and during use with a broad, flat stirrer. Do NOT shake.
- Apply first coat by brush, short nap mohair roller or spray at the recommended coverage rate and in the direction of the grain. Maintain a wet edge to ensure a smooth, even finish. Apply adequate product to end grain and all

Application

edges.

- Allow to dry for a minimum of eight hours.
- If required, fill nail holes, cracks and imperfections with Haymes Woodcare Wood Putty following label instructions. Please ensure that you have selected a Wood Putty to suit your timber colour.
- Lightly sand with 240-grit sandpaper. Remove dust.
- Apply second and subsequent coats, using the method outlined above.

Thinning

Thinning is not recommended. However, under warm conditions, up to 50mL of mineral turpentine can be added per litre of product to ease application. If spraying, add up to 100mL of mineral turpentine per litre to thin. Additional coats may be required to achieve adequate film build after thinning.

Care and Maintenance

Protect the surface from any contact for 24 hours after coating. Avoid abrasive contact for seven days. After seven days, the surface can be cleaned with a mild detergent solution when necessary. Recoat surface with Haymes Woodcare Interior Varnish when coating shows signs of wear and tear.

Storage

Read the Safety Data Sheet (SDS) for this product for specific directions on storage (section 7 of the SDS) and transport (section 10 of the SDS). To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431. Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks. Ensure the container label remains legible for future identification and usage.

Safety & First Aid

Read the Safety Data Sheet (SDS) for this product, prior to using this product. The SDS contains important information on how to use this product safely including hazards and precautions, personal protective equipment, storage and first aid in the event of an emergency. To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431.

If the product is swallowed, phone the Poisons Information Centre on 13 11 26 or contact a Doctor. Keep out of reach of children. Flammable liquid and vapour. Harmful if inhaled. May cause drowsiness or dizziness. Avoid breathing vapours. Only use this product in a well ventilated space and away from ignition sources. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using.

Protect our Environment

Do NOT pour any leftover product down the drain. Retain in a marked, sealed container for future use or disposal via chemical waste collection programs such as Paintback®. Visit www.paintback.com.au for details of your nearest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Important safety information is available on the Safety

Manufacturer's comment

Data Sheet available from Haymes Paint website www.haymepaint.com.au. Further information about other Haymes products recommended to be used in conjunction with this product are available from the website in the form of Product Data Sheets in relation to those products. We are continually updating materials and methods, so please ensure you have the latest information on the Haymes Paint website.

Disclaimer

The information provided in this Product Data Sheet is correct at the time of preparation, but is subject to change. It is your responsibility to check the Haymes Paint website at www.haymepaint.com.au to ensure that you have the most current Product Data Sheet. Product application and performance is affected by environmental conditions at the time of application and drying. Paint applied in conditions outside of what is recommended may dry more slowly or be less durable, or produce a less uniform appearance.

Version

Version and Date Issued	Version 2.0 Date 10/08/2021
Supersedes	Version 1.0 Date 01/11/2016

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Park
Ballarat Vic 3355
Freecall 1800 033 431
www.haymepaint.com.au