

CONCRETE & PAVING PROTECTION

PaveShield Solvent

Product base code: PSS



Product description

Haymes PaveShield Solvent is a multi-purpose solvent used for thinning, clean-up and reactivating previously sealed surfaces with the PaveShield concrete sealer.

Key features & benefits

Reactivating solvent

Thinner and cleaning solvent

Where to use

Substrates:

Correctly prepared concrete, exposed aggregate, patterned & stencilled concrete.

User instructions

- **Thinning**: On bare surfaces (excluding exposed aggregate) use PaveShield solvent to thin the first coat only at a rate of 300mL of clean Haymes PaveShield Solvent per litre of sealer and stir thoroughly.
- Reactivating existing coated surfaces: Apply liberally in small areas at a time and using a stiff bristle broom or brush, scrub into the surface. Allow 1-2 hours before resealing.

Storage

Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a secure, cool, dry, well-ventilated place and out of direct sunlight. Do not expose to temperatures exceeding 60°C. Check regularly for leaks.

Safety Directions & First Aid

SAFETY DIRECTIONS

WARNING – Flammable liquid and vapour. POISON – Harmful if swallowed or inhaled. Keep out of reach of children. Read label before use. Keep away from heat, hot surfaces, open flames and other ignition sources. Exposure via inhalation may cause respiratory irritation, drowsiness or dizziness. Avoid breathing mist, vapour or spray. Causes skin irritation and serious eye irritation. Avoid eye contact and repeated or prolonged skin contact. Wear overalls, safety glasses, impervious gloves and a suitable respirator when mixing and using. Use only in well-ventilated areas. Keep containers tightly closed when not in use.

FIRST AID Instructions

If swallowed, rinse mouth with water. Do NOT induce vomiting. Seek immediate medical advice or call the Poisons Information Centre (Phone 13 11 26). If affected by inhalation, move to fresh air. Apply artificial respiration if not breathing, seek immediate medical assistance. If skin or hair contact occurs, remove contaminated clothing and wash with plenty of soap and water. If irritation occurs, seek medical advice. If eye contact occurs, rinse cautiously with water. Remove contact lenses if present and easy to do so. Continue rinsing. In all cases of eye contact, it is a sensible precaution to seek medical advice. If you continue to experience irritation or feel unwell, seek medical advice or call the Poisons Information Centre.

Protect our environment

Do NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au. We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however, it is the responsibility of those using this information to check that it is current before specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices comply with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded. Document valid unless superseded.

Henry Haymes Pty Ltd A.B.N. 14 004 201 638 Waringa Drive Wendouree Industrial Park Ballarat Vic 3350 Free call 1800 033 431 www.haymespaint.com.au

Date of Preparation 30/10/2020